



**MARINE - INDUSTRIAL**

# ***TECHNICAL DATA***

2705 CONCORD ROAD BELLE CHASSE, LA 70037

PHONE: 504-392-8811 FAX: 504-392-2173

www.royalcoatings.net

---

---

## **EASY KOTE HIGHLIGHTS**

### **Advantages:**

- 1. No sandblasting needed**
- 2. Surface prep – SP-2 or a clean tight rusty surface**
- 3. Water based, non-flammable**
- 4. Less than 10 grams per liter of VOC per gallon**
- 5. Excellent surface tolerant anticorrosive paint**
- 6. Contains anticorrosive compounds**
- 7. Can be torched safely; will not sustain combustion**
- 8. Available in black, grey, or tile red**
- 9. Heat resistant to 300°F (150°C)**
- 10. Should last years in brown and fresh water ballast tanks**
- 11. Easy to use and dries quickly**
- 12. Excellent thixotropic properties in spraying**
- 13. Polymer provides for flexibility and strength**
- 14. Can withstand light foot traffic**
- 15. Excellent paint primer for waterborne paints**
- 16. Can be applied over painted surfaces**
- 17. 60% solids by volume**
- 18. Non hazardous for disposal purposes (It's asphalt)**
- 19. Easy to repair and maintain**
- 20. Outstanding ability to penetrate tight rust**
- 21. Two coat system**
- 22. 70-80 sq. feet per gallon for two coats or (1.75 – 1.9 sq. meters/liter)**
- 23. No solvents**
- 24. No fumes**
- 25. No obnoxious smell**

### **Disadvantages:**

- 1. Inspect for complete drying before filling tank.**
- 2. Premature filling may cause nausea or diarrhea for drinking water purposes.**
- 3. Should not be applied in (COLD WEATHER BELOW 45°F or 7°C) without dehumidification.**
- 4. Do not use externally without top coating with a UV resistant waterborne paint**
- 5. CAUTION: IF using man made water, make sure the pH is adjusted to 7 or higher. Distilled water may cause premature failure of EASY KOTE.**
- 6. Do not use with Cathodic Protection.**