

# EASY DEGREASER

## Water Based Cleaner

- Water Based
- pH Neutral
- Fully Biodegradable
- Virtually Odorless
- Slightly Jelled For Non Sagging
- Removes Hydrocarbon, Vegetable, Lanolin and Calcium Sulfomate Greases and Waxes
- Contains No Phosphates, Chlorinated Hydrocarbons Or Any Harsh Chemicals
- Non-Flammable, Non-Hazardous

### Description:

Easy Degreaser was especially formulated to clean tanks that have residual film of various greases – lanolin, hydrocan, calcium, sulfomate or vegetable. It is usually not necessary to hand scrape excessive film thickness. Simply spray Easy Degreaser with an airless to a WFT of 10 mils (250 microns) or more. Let it soak for 2 – 10 hours and hydro-blast off with 6000 psi or higher. The use of lower pressure with hot water will achieve an even cleaner surface. For very rusty surfaces or for areas where the original film thickness was in excess of 40 mils (1000 microns) a second application may be necessary.

### Specifications:

<b>pH</b>	<b>Neutral</b>
<b>Color</b>	<b>Milky White</b>
<b>Odor</b>	<b>Very Mild</b>
<b>Specific Gravity</b>	<b>.90 ± .03</b>
<b>VOCs</b>	<b>Less than 0.75 lbs./gallon</b>

Easy Degreaser is designed for special project cleaning. It should not be cut with water. In spraying, wear eye protection, gloves and rubber boots.

**\*Always refer to Royal's MSDs before the use of any or our products\***

**Packaging:** Product is available in 55-gallon drums and 5-gallon pails.

For further assistance and information contact:



Royal Coatings Inc.  
2705 Concord Road  
Belle Chasse, LA 70037 USA  
Telephone: (504) 392-8811  
Fax: (504) 392-2173

#### WARNING

It is not recommended for use on vinyl, latex, alkyd or chlorinated rubber surfaces. Always check for compatibility before use. Will not harm epoxies, cement or steel.