

ROYAL UNDERCOAT 5000



MARINE - INDUSTRIAL

Asphaltic Based Liquid Paint

- Asphaltic Emulsion
- Single Component
- Waterborne Safe
- Fast Drying
- Safe & Easy to Use
- Protective Metal Coating

A polymer modified asphaltic water-borne coating for the protection of chassis/frames and other underbody component. Coating provides protection from corrosion, abrasion, and seals out moisture. It improves sound deadening and vibration dampening to metal surfaces.

APPLICATION:

Direct to metal airless spray using a 30:1 with about 40 lbs of inlet air pressure. Surfaces should be clean of oil, dirt, and rust before application. Clean up with soapy water before drying. After drying use a solvent such as mineral spirits.

DRYING:

Dry times will be dependent on substrate temperature, relative humidity, air circulation and film thickness. Full cure in 24 hours @74°F.

Technical Data

Percent solids by weight	52-54%
VOC	0.1#/gallon
Recommended dry film thickness	3-6 mils
HAPS content	None
Flash	Non-flammable
Store Product	Above 50°F

PACKAGING:

55 GALLON DRUMS OR 265 GALLON TOTES

For further information contact: Royal Coatings Inc., 2705 Concord Road
Belle Chasse, LA 70037
Phone: (504) 392-8811 * (504) 392-2173

RV: 07/12