

ROYALCOAT 111

Anti-Skid Additive



PRODUCT DESCRIPTION	Grey dual-mesh aluminum oxide floor coating additive
CHARACTERISTICS	Abrasion resistant aggregate suitable for marine and offshore decks , walkways , engine & fan room floors or other areas with heavy traffic. Blend of 16 and 36 mesh aluminum oxide to provide a heavy non-skid surface
INSTRUCTIONS FOR USE	<p>Rate of 1 LB RoyalCoat 111 per 10 liter pail of coating.</p> <p>Add directly to Uni-Pak pail of Easy Flex Grey (product code 422) during mixing or broadcast into applied film for a more aggressive non-slip-surface</p> <p>Always add to pail after part A and B have been blended</p> <p>Mix frequently to avoid settling</p> <p>Apply with a mastic gun , short nap roller or brush. If choosing to broadcast aggregate then apply coating per technical data sheet for that product</p>
SURFACE PREPARATIONS	Refer to Easy Flex Grey product data sheet
PACKAGE SIZE	RoyalCoat 111 is packaged in 1 LB cans with 16 cans per box
PRODUCT CODE	111
AVAILABILITY	Worldwide

IMPORTANT NOTE

The information contained in this data sheet is to the best of our knowledge true and accurate; but all recommendations or suggestions are made without guarantee, since the conditions of use are beyond our control. Each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate. We hereby disclaim any warranties or representations, express or implied, by operation of law or otherwise, including, without limitation, any implied warranty of merchantability or fitness for a particular purpose.

www.royalcoatings.net