

EASY KOTE



MARINE - INDUSTRIAL

Asphaltic Based Liquid Paint

- Asphaltic Emulsion
- Single Component
- Waterborne Safe
- Fast Drying
- Safe & Easy to Use
- Protective Metal Coating
- 15 Years Experience on over 8000 Barges



DRINKING WATER SYSTEM COMPONENTS
ANSI/NSF 61
5N16, 6N21



A polymer modified and mineral filled asphaltic waterborne coating for the protection of chassis/frames and other underbody parts. This is our best performing undercoat that gives excellent long term flexibility. The coating provides protection from corrosion, abrasion and seals out moisture. It also improves sound deadening and vibration dampening to metal surfaces.

APPLICATION:

Direct to metal airless spray using a 30:1 with about 40 lbs of inlet air pressure. Surfaces should be clean of oil, dirt, and rust before application. Clean up with soapy water before drying. After drying use a solvent such as mineral spirits.

DRYING:

Dry times will be dependent on substrate temperature, relative humidity, air circulation and film thickness. Full cure in 24 hours @74°F.

Technical Data

Percent solids by weight	68- 70%
by volume	64-66%
VOC	0.1#/gallon
Recommended wet film thickness	12-24 mils
HAPS content	None
Flash	Non-flammable
Store above	50°F
Colors	Black or Grey
2000 Hr. Salt Fog	Passed

PACKAGING:

55 GALLON DRUMS OR 330 GALLON TOTES. PROTECT FROM FREEZING

For further information contact: Royal Coatings Inc., 2705 Concord Road
Belle Chasse, LA 70037
Phone: (504) 392-8811 * (504) 392-2173