

# EZ-SOLV



MARINE - INDUSTRIAL

## A Multipurpose Clean-Up Solvent

- 100% Aromatic Solvent
- Very Low Odor
- High Solvency Power
- Low Volatility and Cost
- High Flash Point – Non Hazardous
- Miscible in alcohols, ethers, ketones and most hydrocarbons
- Very Low Evaporation
- 100% Hazardous Air Pollutants Free
- Zero VOCs

EZ-Solv is an excellent choice for cleaning paint lines and equipment used in painting. It is an excellent choice for dissolving uncured epoxy, two-part urethanes and polyesters. The low volatility of EZ-Solv prevents the solubilized coating from re-adhering to substrates. This also allows it to be re-used after filtering.

### EXPOSURE:

As with any organic solvent, EZ-Solv should be used with adequate ventilation and direct skin contact should be avoided by proper use of protective equipment. EZ-Solv may cause eye and respiratory tract irritation. When significant potential for eye contact exists, wear chemical goggles.

### STORAGE:

EZ-Solv may be stored and handled without special precautions. EZ-Solv is non-corrosive, photochemically non-reactive, and is not classified as a hazardous material by DOT.

### COMPATIBILITY

It is important to select compatible seals and gaskets. EZ-Solv is compatible with Teflon, nylon, silicone, neoprene, ethylene propylene polymer, polyethylene and polypropylene. Avoid the use of NBR rubber, fluoro-elastomers and polyurethane types.

### DISPOSAL:

Consult with local authorities or follow rules as known for regular solvents.

### Technical Data

Specific Gravity	0.99.
Solubility in Water	0%
Flash Point	300°F/150°C

**CAUTION:** Do not use to thin any paint.

For further information contact: Royal Coatings, Inc, 2705 Concord Road, Belle Chasse, LA 70037  
Phone: (504) 392-8811 \* (504) 392-2173