

EASY KOTE HIGHLIGHT SHEET

Advantages

- 1). No sandblasting needed
- 2). Surface prep - SP-2 or a clean tight rusty surface
- 3). Water based, non flammable
- 4). Less than 10 grams per liter of VOC per gallon
- 5). Excellent surface tolerant anticorrosive paint
- 6). Contains anticorrosive compounds
- 7). Can be torched safely: will not sustain combustion
- 8). Available in black and grey
- 9). Heat resistant to 300 ° F (150 ° C)
- 10). Easy to use and dries quickly
- 11). Excellent thixotropic properties in spraying
- 12). Polymer provides for flexibility and strength
- 13). Can withstand light foot traffic
- 14). Excellent paint primer for waterborne paints
- 15). Can be applied over painted surfaces
- 16). 70 % solids by volume
- 17). Non hazardous for disposal purposes (It's asphalt!)
- 18). Easy to repair and maintain
- 19). Outstanding ability to penetrate tight rust
- 20). Two coat system
- 21). 70- 80 sq. feet per gallon for two coats or (1.75 - 1.9 sq. meters/liter)
- 22). No solvents
- 23). No fumes
- 24). No obnoxious smell

Disadvantages

- 1). Inspect for complete drying before filling tank
- 2). Premature filling may cause nausea or diarrhea for drinking water purposes
- 3). Should not be applied in cold weather (below 45°F or 7°C) without dehumidification.
- 4). Do not use externally without top coating with a UV resistant waterborne paint.
- 5). CAUTION: if using man made water, make sure the pH is adjusted to 7 or higher. Distilled water may cause premature failure of EASY KOTE9
- 6). Do not use with Cathodic Protection

